

**ROOFING PERMIT INFORMATION**

Application # \_\_\_\_\_

Please fill in the following.

Roof Type:

- Asphalt
- Built Up
- Clay/Cement Tile
- Fiberglass
- Membrane, commercial
- Membrane, residential
- Metal
- Wood

\*Attach Manufacturer’s specification sheets for roofing material and edge securement.  
**2015 IBC, Article 1504.5 Edge Securement.** Edge securement for low slope roofs. Low slope built up, modified bitumen and single-ply roof system metal edge securement, except gutters, shall be designed and installed for wind loads in accordance with Chapter 16 and tested for resistance in accordance with test methods RE-1, RE-2, RE-3 of ANSI/SPRI ES-1 except V/ult wind speed shall be determined from Figure 1609.3(1), 1609.3(2), 1609.3(3) as applicable.

Number of Existing Layers: \_\_\_\_\_

Is Roof being Stripped?  Yes  No

Is Roof being Resheathed?  Yes  No

Number of Squares: \_\_\_\_\_

Is Ice and Water being installed?  Yes  No Full Coverage?  Yes  No

Plywood Seams being taped?  Yes  No **(2015 IRC R905.1.1)**

Is Roof Ventilation present?  Yes  No\* Type:  Ridge  Gable  Soffit  
\*If 'No', how will roof ventilation be addressed? \_\_\_\_\_.

**Roof Ventilation is required per 2015 IRC, Section R806, 2015 IBC Section 1203.**

**Kickout Flashing required per 2015 IRC, Section 903.2.1.**

**R903.2.1 Locations.** Flashings shall be installed at wall and roof intersections, wherever there is a change in roof slope or direction and around roof openings. A flashing shall be installed to divert the water away from where the eave of a sloped roof intersects a vertical sidewall. Where flashing is of metal, the metal shall be corrosion resistant with a thickness of not less than 0.019” (0.5mm)(No. 26 Galvanized Sheet).

Applicant \_\_\_\_\_ Signature \_\_\_\_\_ Date \_\_\_\_\_